



## QSA<sup>SM</sup> – Detect Internal Sludge and Varnish Build-up

Varnish is composed of lubricant degradation by-products and can cause a host of performance problems. Sensitive hydraulic and turbine systems can come to an abrupt halt if varnish is not detected. Detecting this threat has previously been limited to physical inspections which force a shutdown of the system being inspected, resulting in loss of availability and revenue.

### In Response to This Problem

Analysts, Inc., has developed an innovative test – **QSA<sup>SM</sup>** – Quantitative Spectrophotometric Analysis – to accurately determine a used lubricant's likelihood to promote harmful sludge and varnish build-up.

The QSA program is based on new procedures that determine a specific single-temperature rating for the used lubricant. Based on the lubricant type and the application, the basic QSA rating allows a trained diagnostician to determine the presence or likelihood of internal sludge and varnish build-up.

When a wider view of a lubricant's varnish profile is justified, QSA Advanced is the key to anticipating the oil's thermal-response curve. Most lubricants provide good performance at normal operating temperatures. However, varnish build-up at higher or lower temperatures is an emerging problem, particularly in hydraulic and turbine applications. The consequences are time consuming and costly. System failures due to varnish problems can include sticking or seized control servos, restricted oil flow, increased oil temperatures, plugged or partially blocked strainers, overall deposit formation, increased wear and component failures.

The causes of varnish deposition – which include thermal degradation, severe oxidation and coking – are natural occurrences in the operation of heavy-duty hydraulic and turbine operations. Historically, visual inspections were performed to find the varnish build-up. Commercial oil analysis – while an essential tool in proactive maintenance through wear, contamination and lube condition monitoring – has not offered a reliable, cost-effective procedure to identify varnishing conditions and varnish potential – until now.

### The Impact of Varnish in a Lubrication System

There are numerous types of insoluble contaminants found in lubricating systems. Insoluble contaminants are those materials that will not dissolve in the oil. The two most general classifications of insoluble contaminants are hard contaminants, such as dirt, debris and wear particles, and soft contaminants, composed of the various oil degradation by-products.

Varnish originates from these soft contaminants. It is a thin, insoluble film that over time deposits throughout the internal surfaces of a lubrication system. The degradation process accelerates as the lubricant undergoes continued exposure to air, water, and high temperatures.

The presence of varnish in hydraulic and lubrication systems causes many serious problems, including but not limited to the following:

#### ➔ **Reduced clearance zones affecting lubrication**

Often, this means a transition from full-film to boundary lubrication, resulting in increased wear of pumps, bearings, gears and valves

- ➔ **Increased friction**  
This results in higher energy requirements, and can cause valves to stick or seize
- ➔ **Higher operating temperatures**  
Varnish acts as an insulator, decreasing the cooling effect of heat exchangers
- ➔ **Restriction or impedance of oil flow**  
Varnish clogs strainers, filters and lines
- ➔ **Increased wear rates**  
Varnish captures hard contaminants, creating an abrasive surface that accelerates wear
- ➔ **System corrosion and accelerated degradation due to acidic constituents**
- ➔ **Increased maintenance resources and costs required to clean varnished systems**

-----

All of these factors contribute to conditions that often end in failure. At a utility company, a sticking control valve in a gas-turbine engine can cause the unit to go offline, with a potential result of hundreds of thousands of dollars in lost revenue alone. At a manufacturing facility, deposits in an injection-molding machine's control servos may cause the system to malfunction, resulting in damaged finished parts. This may cost the operation many thousands of dollars in lost revenue, time and material.



## QSA functions best as part of a complete oil analysis program

Recommended complete testing program:

- ➔ **Spectrochemical Analysis**  
Atomic Emission, ppm by wt.  
21 elements, D6595
- ➔ **Physical Analysis**  
QSA  
Viscosity, 40° C, cSt, D445  
Water, ppm, Karl Fischer, D6304  
Acid Number, mg KOH/g, D664 or D974  
Particle-Count, count/ml, ISO11171 (cal), ISO4406-99 (report)  
Ferrography (optional)

## Call Today

See for yourself how Analysts' QSA and fluid analysis services will help build your equipment productivity. Call your Analysts representative or the lab nearest you. Or visit us at [www.analystsinc.com](http://www.analystsinc.com).

-----

LOS ANGELES, CA	800-424-0099
HOUSTON, TX	800-248-7778
CHICAGO, IL	800-222-0071
ATLANTA, GA	800-241-6315
LOUISVILLE, KY	888-491-6063